

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 10466690 |
| Valid tyre size | 435 / 50 R 19.5 |
| LI / SI / PR | 160 J, 20 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | PRO TL98 |



WINDPOWER
Get Your Job Done

Notes and features

- The Windpower PRO TL98 is a truck tyre for the trailer axle for use in long-distance transport.
- Its optimised tread design ensures slow wear and a long service life.
- The special reinforced bead construction with steel core (BWC = Bead Wrapped Chafer) protects the tyre from lateral impact damage even under difficult load conditions.
- Particularly high-quality, extremely strong cord plies (SHT = Super High Tensile Cord) ensure excellent handling and low rolling resistance.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 10466690 |
| EAN | 4040658097331 |
| Valid tyre size | 435 / 50 R 19.5 |
| LI / SI / PR | 160 J, 20 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | PRO TL98 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | C |
| Wet grip | B |
| Rolling noise [db]. | 73 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 66,38 |
| Recommended rim size | 14.00 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 430 |
| Outer diameter of tyre [mm]. | 920 |
| Stat. radius (SLR) [mm] | 428 |
| Rolling circumference [mm]. | 2806 |
| Tread depth (mm) | 12,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 J | 4500 | 100 | Single | 9,00 | |