

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 10466693 |
| Valid tyre size | 445 / 65 R 22.5 |
| LI / SI / PR | 169 K, 20 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | WTR 69 |



WINDPOWER
Get Your Job Done

Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound, flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 10466693 |
| EAN | 4040658087943 |
| Valid tyre size | 445 / 65 R 22.5 |
| LI / SI / PR | 169 K, 20 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | WTR 69 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | C |
| Wet grip | B |
| Rolling noise [db]. | 73 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 95,10 |
| Recommended rim size | 13.00 |
| Permitted rim size | 14.00 |
| Maximum air pressure [bar]. | 8,30 |
| Section width (mm) | 443 |
| Outer diameter of tyre [mm]. | 1147 |
| Stat. radius (SLR) [mm] | 521 |
| Speed Radius Index (SRI) | 550 |
| Rolling circumference [mm]. | 3498 |

| | |
|------------------|------|
| Tread depth (mm) | 16,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 K | 5800 | 110 | Single | 8,30 | |