Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10466700	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	152 / 148 M (154 / 150 L), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDW 80	





Notes and features

- Winter drive wheel tyre with reliable grip and traction.
- Extra-wide, deep tread pattern bed / open tyre shoulder.
- Excellent self-cleaning properties.

- Tread compound adapted to winter use. •
- Reduced operating costs due to long-life compound.
- Retreadable casing.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10466700		
EAN	4040658055706		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	152 / 148 M (154 / 150 L), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WDW 80		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	E		
Wet grip	C		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	72,30		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	8,30		
Section width (mm)	312		
Outer diameter of tyre [mm].	1032		
Stat. radius (SLR) [mm]	468		
Rolling circumference [mm].	3148		
Tread depth (mm)	24,0		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	8,30	
154 L	3750	120	Single	8,30	
148 M	3150	130	Twin	8,30	
150 L	3350	120	Twin	8,30	

19.09.2024