

TYRES

Product group	Tyres	
Item number	10466702	
Valid tyre size	alid tyre size 315 / 70 R 22.5	
LI / SI / PR 156 / 150 L (154 / 150 M), 18 PR		
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSW 80	



WINDP()WER

Notes and features

- Front axle tyre with reliable grip and traction in winter operations, also suitable for the transport of dangerous goods.
- Can be used as trailer tyre as well.
- Traction grip block and modern sipe design.

- Wide, deep tread pattern / half-open tyre shoulder.
- Tread compound adapted to winter use.
- Winter tyre with snow flake symbol.
- Retreadable casing.



Technical Informations

Item number	10466702		
EAN	4040658063954		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WSW 80		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA		
Rolling resistance	С		
Wet grip	В		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	61,70		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	8,30		
Section width (mm)	302		
Outer diameter of tyre [mm].	1016		
Stat. radius (SLR) [mm]	467		
Rolling circumference [mm].	3099		
Tread depth (mm)	16,5		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	10	Single	8,30	
154 M	3750	130	Single	8,30	
150 L	3350	120	Twin	8,30	
150 M	3350	130	Twin	8,30	