

TYRES

Product group	Tyres	
Item number	10466703	
Valid tyre size	alid tyre size 315 / 80 R 22.5	
LI / SI / PR	154 / 151 M (156 / 150 L), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDW 80	





Notes and features

- Winter drive wheel tyre with reliable grip and traction.
- Extra-wide, deep tread pattern bed / open tyre shoulder.
- Excellent self-cleaning properties.

- Tread compound adapted to winter use.
- Reduced operating costs due to long-life compound.
- Retreadable casing.



Technical Informations

Item number	10466703		
EAN	4040658055713		
Valid tyre size	315 / 80 R 22.5		
LI / SI / PR	154 / 151 M (156 / 150 L), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WDW 80		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	Е		
Wet grip	С		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	number ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	78,70		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	8,30		
Section width (mm)	315		
Outer diameter of tyre [mm].	1096		
Stat. radius (SLR) [mm]	505		
Rolling circumference [mm].	3343		
Tread depth (mm)	24,0		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No	
---------	----	--

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,30	
156 L	4000	120	Single	8,30	
151 M	3450	130	Twin	8,30	
150 L	3350	120	Twin	8,30	