# Bohnenkamp Moving Professionals

20.09.2024

### **TYRES**

Product group	Tyres	
Item number	10466709	
Valid tyre size	275 / 70 R 22.5	
LI / SI / PR	148 / 145 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 36	





#### Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10466709
EAN	4040658089923
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	47,20
Recommended rim size	8.25
Permitted rim size	9.00, 7.50
Maximum air pressure [bar].	9,00
Section width (mm)	269
Outer diameter of tyre [mm].	962
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2934
Tread depth (mm)	15,0

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

### Bohnenkamp Moving Professionals

20.09.2024

E-Ready

No

#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 M	3150	130	Single	9,00	
145 M	2900	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.