

## TYRES

|                 |                                  |
|-----------------|----------------------------------|
| Product group   | Tyres                            |
| Item number     | 10466714                         |
| Valid tyre size | 315 / 70 R 22.5                  |
| LI / SI / PR    | 152 / 148 M (154 / 150 L), 18 PR |
| TL/TT           | TL                               |
| Brand           | Windpower                        |
| Tread pattern   | WDL 60                           |



**WINDPOWER**  
Get Your Job Done

## Notes and features

- Latest-generation, modern drive wheel tyre for long-haul trucking.
- Reduced operating costs due to long-life compound.
- More efficient fuel consumption due to reduced rolling resistance.

## Technical Informations

|                              |                                  |
|------------------------------|----------------------------------|
| Item number                  | 10466714                         |
| EAN                          | 4040658084256                    |
| Valid tyre size              | 315 / 70 R 22.5                  |
| LI / SI / PR                 | 152 / 148 M (154 / 150 L), 18 PR |
| TL/TT                        | TL                               |
| Brand                        | Windpower                        |
| Tread pattern                | WDL 60                           |
| M+S                          | M+S                              |
| 3PMSF                        | 3PMSF                            |
| Axle position truck          | RA                               |
| Rolling resistance           | C                                |
| Wet grip                     | B                                |
| Rolling noise [db].          | 74                               |
| Rolling noise level          | B                                |
| Antistatic                   | No                               |
| Tyre colour                  | Black                            |
| ECE regulation number        | ECE 54,ECE 117                   |
| Nettogewicht [kg] (gültig)   | 64,70                            |
| Recommended rim size         | 9.00                             |
| Permitted rim size           | 9.75                             |
| Maximum air pressure [bar].  | 8,30                             |
| Section width (mm)           | 316                              |
| Outer diameter of tyre [mm]. | 1020                             |
| Stat. radius (SLR) [mm]      | 475                              |
| Rolling circumference [mm].  | 3114                             |
| Tread depth (mm)             | 18,0                             |

E-Ready

No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 M | 3550               | 130          | Single        | 8,30                     |              |
| 154 L | 3750               | 120          | Single        | 8,30                     |              |
| 148 M | 3150               | 130          | Twin          | 8,30                     |              |
| 150 L | 3350               | 120          | Twin          | 8,30                     |              |