

TYRES

Product group	Tyres
Item number	10466718
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

Technical Informations

Item number	10466718
EAN	4040658089985
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	59,90
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	302
Outer diameter of tyre [mm].	1046
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3190
Tread depth (mm)	15,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	120	Single	9,00	
149 M	3250	130	Twin	9,00	