

TYRES

Product group	Tyres
Item number	10466719
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSW 80



WINDPOWER
Get Your Job Done

Notes and features

- Front axle tyre with reliable grip and traction in winter operations, also suitable for the transport of dangerous goods.
- Can be used as trailer tyre as well.
- Traction grip block and modern sipe design.
- Wide, deep tread pattern / half-open tyre shoulder.
- Tread compound adapted to winter use.
- Winter tyre with snow flake symbol.
- Retreadable casing.

Technical Informations

Item number	10466719
EAN	4040658084287
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSW 80
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	68,40
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,30
Section width (mm)	316
Outer diameter of tyre [mm].	1081
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3300
Tread depth (mm)	16,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,30	
154 M	3750	130	Single	9,30	
150 L	3350	120	Twin	9,30	
150 M	3350	130	Twin	9,30	