

TYRES

Product group	Tyres
Item number	10466723
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 150 M (156 / 150 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 52



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- Excellent traction due to hexagonal tread pattern design.
- Outstanding self-cleaning due to open tread pattern design at the shoulder.
- High resistance to cuts due to multi-layer casing.
- Low cost per mile due to long service life.

Technical Informations

Item number	10466723
EAN	4040658059247
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 150 M (156 / 150 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 52
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,90
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,30
Section width (mm)	317
Outer diameter of tyre [mm].	1088
Stat. radius (SLR) [mm]	508
Rolling circumference [mm].	3318
Tread depth (mm)	19,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,30	
156 L	4000	120	Single	8,30	
151 M	3450	130	Twin	8,30	
150 L	3350	120	Twin	8,30	