

TYRES

Product group	Tyres
Item number	10466725
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 55



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre for the drive axle (especially for tipper trucks).
- Extra-deep lug profile (23 mm) with cut- and tear-proof rubber compound.
- Excellent water displacement due to open tyre shoulder design.

Technical Informations

Item number	10466725
EAN	4040658080814
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 55
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,90
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,30
Section width (mm)	317
Outer diameter of tyre [mm].	1097
Stat. radius (SLR) [mm]	508
Rolling circumference [mm].	3346
Tread depth (mm)	23,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,30	
150 K	3350	110	Twin	8,30	