Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10466731	
Valid tyre size	385 / 55 R 22.5	
LI / SI / PR	158 L (160 K), 20 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSW 80	



Notes and features

- Front axle tyre with reliable grip and traction in winter operations, also suitable for the transport of dangerous goods.
- Can be used as trailer tyre as well.
- Traction grip block and modern sipe design.

- Wide, deep tread pattern / half-open tyre shoulder.
- Tread compound adapted to winter use.
- Winter tyre with snow flake symbol.
- Retreadable casing.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10466731
EAN	4040658078545
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	158 L (160 K), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSW 80
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С
Wet grip	С
Rolling noise [db].	74
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,50
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	385
Outer diameter of tyre [mm].	1004
Stat. radius (SLR) [mm]	458
Rolling circumference [mm].	3042
Tread depth (mm)	13,5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

19.09.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,00	
160 K	4500	110	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.