

TYRES

Product group	Tyres	
Item number	10466737	
Valid tyre size	385 / 65 R 22.5	
LI / SI / PR	164 K (158 L), 20 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSW 80	





Notes and features

- Front axle tyre with reliable grip and traction in winter operations, also suitable for the transport of dangerous goods.
- Can be used as trailer tyre as well.
- Traction grip block and modern sipe design.

- Wide, deep tread pattern / half-open tyre shoulder.
- Tread compound adapted to winter use.
- Winter tyre with snow flake symbol.
- Retreadable casing.



Technical Informations

Item number	10466737
EAN	4040658078033
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSW 80
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С
Wet grip	С
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	74,60
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	385
Outer diameter of tyre [mm].	1064
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3245
Tread depth (mm)	13,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	
158 L	4250	120	Single	9,00	