

## TYRES

Product group	Tyres
Item number	10466744
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69+



**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound. Flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder for protection against collision and sidewall damage.
- Improved casing design for better comfort, high tyre stability and reduced internal heat development.
- Slush and snow marking.
- Retreadable casing.

## Technical Informations

Item number	10466744
EAN	4040658087936
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69+
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	76,30
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	384
Outer diameter of tyre [mm].	1069
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3260
Tread depth (mm)	16,8

---

E-Ready	No
---------	----

---

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	
158 L	4250	120	Single	9,00	