

TYRES

Product group	Tyres
Item number	10466746
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466746
EAN	4040658097225
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	75,90
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	387
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3264
Tread depth (mm)	16,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	
158 L	4250	120	Single	9,00	