

TYRES

Product group	Tyres
Item number	10466747
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO TR88



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- The Windpower PRO TR88 is a truck tyre for drive axles for use in regional transport.
- Its optimum tread design ensures even pressure distribution for slow wear and a long service life.
- The special reinforced bead construction with steel core (BWC = Bead Wrapped Chafer) protects the tyre from lateral impact damage even under difficult load conditions.
- Particularly high-quality, extremely strong cord plies (SHT = Super High Tensile Cord) ensure excellent handling and low rolling resistance.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.

Technical Informations

Item number	10466747
EAN	4040658097348
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO TR88
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	77,67
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	388
Outer diameter of tyre [mm].	1069
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3260
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	
158 L	4250	120	Single	9,00	