

## **TYRES**

Product group	Tyres	
Item number	10466747	
Valid tyre size	385 / 65 R 22.5	
LI / SI / PR	164 K (158 L), 20 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	PRO TR88	





## Notes and features

- The Windpower PRO TR88 is a truck tyre for drive axles for use in regional transport.
- Its optimum tread design ensures even pressure distribution for slow wear and a long service life.
- The special reinforced bead construction with steel core (BWC = Bead Wrapped Chafer) protects the tyre from lateral impact damage even under difficult load conditions.
- Particularly high-quality, extremely strong cord plies (SHT = Super High Tensile Cord) ensure excellent handling and low rolling resistance.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.



## **Technical Informations**

Item number	10466747
EAN	4040658097348
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K (158 L), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO TR88
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	В
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	77,67
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	388
Outer diameter of tyre [mm].	1069
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3260
Tread depth (mm)	16,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	
158 L	4250	120	Single	9,00	