

TYRES

Product group	Tyres
Item number	10466761
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36



WINDPOWER
Get Your Job Done

Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

Technical Informations

Item number	10466761
EAN	4040658089954
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	68,40
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	1082
Stat. radius (SLR) [mm]	501
Rolling circumference [mm].	3300
Tread depth (mm)	16,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,00	
154 M	3750	130	Single	9,00	
150 L	3350	120	Twin	9,00	
150 M	3350	130	Twin	9,00	