

TYRES

Product group	Tyres
Item number	10466762
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 151 L (156 / 150 K), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 52



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre for all wheel positions on- and off-road.
- Cut- and crack-resistant rubber compound for robust applications.
- Optimised tread pattern design with very good self-cleaning properties.
- WINDPOWER WGC 52.

Technical Informations

Item number	10466762
EAN	4040658089992
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 151 L (156 / 150 K), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 52
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	75
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	67,60
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,30
Section width (mm)	318
Outer diameter of tyre [mm].	1082
Stat. radius (SLR) [mm]	508
Rolling circumference [mm].	3300
Tread depth (mm)	16,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	8,30	
156 K	4000	110	Single	8,30	
151 L	3450	120	Twin	8,30	
150 K	3350	110	Twin	8,30	