Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10466763	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSL 60	





Notes and features

- Modern steering axle tyre of the newest generation for • long-haul transport.
- Safe and quiet handling on wet and dry roads. •
- Optimised running smoothness and tracking due to more . transverse sipes.
- Increased braking force. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	10466763		
EAN	4040658090721		
Valid tyre size	315 / 80 R 22.5		
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WSL 60		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA		
Rolling resistance	D		
Wet grip	В		
Rolling noise [db].	72		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	66,70		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	8,30		
Section width (mm)	317		
Outer diameter of tyre [mm].	1082		
Stat. radius (SLR) [mm]	497		
Rolling circumference [mm].	3300		
Tread depth (mm)	14,5		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	8,30	
154 M	3750	130	Single	8,30	
150 L	3350	120	Twin	8,30	
150 M	3350	130	Twin	8,30	

20.09.2024