

## TYRES

Product group	Tyres
Item number	10466764
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR85



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER**  
Get Your Job Done

## Technical Informations

Item number	10466764
EAN	4040658097355
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR85
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	C

Wet grip	C
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	72,16
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	316
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	506
Rolling circumference [mm].	3325
Tread depth (mm)	21,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	8,50	
154 M	3750	130	Single	8,50	
150 L	3350	120	Twin	8,50	
150 M	3350	130	Twin	8,50	