

TYRES

Product group	Tyres	
Item number	10466765	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	PRO SR80	





Technical Informations

Item number	10466765		
EAN	4040658097362		
Valid tyre size	315 / 80 R 22.5		
LI / SI / PR	158 / 150 L (154 / 150 M), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	PRO SR80		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA		
Rolling resistance	В		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	В
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	66,27
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	317
Outer diameter of tyre [mm].	1081
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3297
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,00	
154 M	3750	130	Single	9,00	
150 L	3350	120	Twin	9,00	
150 M	3350	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.