

TYRES

Product group	Tyres
Item number	10468078
Valid tyre size	8.25 R 20
LI / SI / PR	136 / 134 K, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10468078
EAN	4040658089688
Valid tyre size	8.25 R 20
LI / SI / PR	136 / 134 K, 14 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 78 A
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	50,54
Recommended rim size	6.50
Permitted rim size	6.50T, 7.0
Maximum air pressure [bar].	8,30
Section width (mm)	232
Outer diameter of tyre [mm].	967
Stat. radius (SLR) [mm]	454

Rolling circumference [mm].	2949
Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 K	2240	110	Single	8,30	
134 K	2120	110	Twin	8,30	