

TYRES

Product group	Tyres
Item number	10468107
Valid tyre size	10.00 R 20
LI / SI / PR	149 / 146 K, 18 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10468107
EAN	4040658091377
Valid tyre size	10.00 R 20
LI / SI / PR	149 / 146 K, 18 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 78 A
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	58,05
Recommended rim size	7.50
Permitted rim size	7.50V, 8.00
Maximum air pressure [bar].	9,30
Section width (mm)	273
Outer diameter of tyre [mm].	1055
Stat. radius (SLR) [mm]	478

Rolling circumference [mm].	3218
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 K	3250	110	Single	9,30	
146 K	3000	110	Twin	9,30	