

## TYRES

Product group	Tyres
Item number	10468182
Valid tyre size	12.00 R 20
LI / SI / PR	154 / 151 K, 18 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 08



**WINDPOWER**  
Get Your Job Done

## Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

## Technical Informations

Item number	10468182
EAN	4040658089732
Valid tyre size	12.00 R 20
LI / SI / PR	154 / 151 K, 18 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 179 A
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	89,50
Recommended rim size	8.50
Permitted rim size	8.50V, 9.0
Maximum air pressure [bar].	8,30
Section width (mm)	310
Outer diameter of tyre [mm].	1123
Stat. radius (SLR) [mm]	520

Rolling circumference [mm].	3425
Tread depth (mm)	17,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 K	3750	110	Single	8,30	
151 K	3450	110	Twin	8,30	