

TYRES

Product group	Tyres
Item number	10468192
Valid tyre size	12.00 R 24
LI / SI / PR	160 / 157 K, 20 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 52



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre for all wheel positions on- and off-road.
- Cut- and crack-resistant rubber compound for robust applications.
- Optimised tread pattern design with very good self-cleaning properties.
- WINDPOWER WGC 52.

Technical Informations

Item number	10468192
EAN	4040658095726
Valid tyre size	12.00 R 24
LI / SI / PR	160 / 157 K, 20 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 179 A
Brand	Windpower
Tread pattern	WGC 52
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	88,10
Recommended rim size	8.50
Permitted rim size	8.50V, 9.00
Maximum air pressure [bar].	9,00
Section width (mm)	314
Outer diameter of tyre [mm].	1224
Stat. radius (SLR) [mm]	567

Rolling circumference [mm].	3733
Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
157 K	4125	110	Twin	9,00	