# Bohnenkamp Moving Professionals

#### **TYRES**

| Product group   | Tyres         |
|-----------------|---------------|
| Item number     | 10485026      |
| Valid tyre size | 385 / 95 R 25 |
| LI / SI / PR    | 170 G         |
| TL/TT           | TL            |
| Brand           | Windpower     |
| Tread pattern   | W 728+        |



#### Notes and features

- The Windpower W 728+ is a modern crane tyre for use on . mobile cranes on- and off-road.
- The special tread pattern provides very good wear • properties.
- Its innovative rubber compound ensures increased wear • resistance and a long tyre life.
- The tyre provides high ride comfort and low rolling • resistance for reduced fuel consumption.
- The tyre has an M+S (mud + snow) marking.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 10485026      |
|------------------------------|---------------|
|                              |               |
| EAN                          | 4040658090745 |
| Valid tyre size              | 385 / 95 R 25 |
| Alternative size 1           | 14.00R25      |
| LI / SI / PR                 | 170 G         |
| TL/TT                        | ть            |
| Brand                        | Windpower     |
| Tread pattern                | W 728+        |
| M+S                          | M+S           |
| TRA Code                     | E2            |
| Star Rating                  | ***           |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 54        |
| Nettogewicht [kg] (gültig)   | 157,20        |
| Recommended rim size         | 10.00/1.5     |
| Maximum air pressure [bar].  | 9,00          |
| Section width (mm)           | 389           |
| Outer diameter of tyre [mm]. | 1363          |
| Stat. radius (SLR) [mm]      | 600           |
| Tread depth (mm)             | 23,5          |
| E-Ready                      | No            |

### Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 170 G | 6000               | 90           |               | 9,00                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.