

TYRES

Product group	Tyres	
Item number	10485031	
Valid tyre size	15.5 R 25	
LI / SI / PR	176 A2 / 160 B	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 732	





Notes and features

- The Windpower W 732 in the E3**/L3** version is a tyre for wheel loaders and dumpers.
- The tyre provides first-class traction on difficult surfaces and high stability.
- Thanks to its cut-resistant rubber compound, the tyre is perfectly protected against cuts.
- Attention: only approved for mounting on multi-part rim.



Technical Informations

Item number	10485031
EAN	4040658090905
Valid tyre size	15.5 R 25
Alternative size 1	385/80R25
LI / SI / PR	176 A2 / 160 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 732
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	146,00
Recommended rim size	12.00/1.3
Maximum air pressure [bar].	6,00
Section width (mm)	404
Outer diameter of tyre [mm].	1272
Stat. radius (SLR) [mm]	560
Tread depth (mm)	27,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A2	7100	10		6,00	
160 B	4500	50		4,75	