

TYRES

Product group	Tyres	
Item number	10485037	
Valid tyre size	16.00 R 25	
LI / SI / PR	200 A5	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 847	



WIND?()WER **Get Your Job Done**

Notes and features

- The Windpower W847 IND-4 has a specially-shaped tyre
- Its particularly low-wear and low-heat-generating rubber compound ensures a long service life.
- The robust sidewalls provide very good stability.
- The tyre is best suited for use in ports on e.g. forklifts and reach stackers.
- Attention: only approved for mounting on multi-part rim.



Technical Informations

Item number	10485037
EAN	4040658082115
Valid tyre size	16.00 R 25
Alternative size 1	445/95R25
LI / SI / PR	200 A5
TL/TT	TL
Brand	Windpower
Tread pattern	W 847
TRA Code	IND4
Star Rating	***
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	320,20
Recommended rim size	11.25/2.0
Maximum air pressure [bar].	10,00
Section width (mm)	430
Outer diameter of tyre [mm].	1552
Tread depth (mm)	53,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
200 A5	14000	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.