Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10485040
Valid tyre size	17.5 R 25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 755



Notes and features

- The Windpower W755 has a durable L-5 tread pattern for . demanding applications.
- The cut- and puncture-resistant tread compound ensures ٠ a long service life for the tyre.
- The robust sidewalls provide very good stability.
- The tyre is best suited for wheel loaders on construction • sites, in recycling operations as well as tunnelling and mining.
- Attention: only approved for mounting on multi-part rim. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	10485040
EAN	4040658055744
Valid tyre size	17.5 R 25
Alternative size 1	445/80R25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 755
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	302,50
Recommended rim size	14.00/1.5
Maximum air pressure [bar].	6,00
Section width (mm)	445
Outer diameter of tyre [mm].	1415
Rolling circumference [mm].	4240
Tread depth (mm)	64,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.