

TYRES

Product group	Tyres	
Item number	10485047	
Valid tyre size	18.00 R 25	
LI / SI / PR	204 A2 / 185 B	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 741	





Notes and features

- With its deep E-4 tread pattern, the Windpower W741 offers excellent wear resistance and thus guarantees a long service life.
- The special, low heat-developing rubber compound is most suitable for use with dumpers and levellers.
- For applications in the most diverse working conditions and on surfaces such as mud, rock and sand.
- Attention: mounting on multi-piece rim only.



Technical Informations

Item number	10485047
EAN	4040658065248
Valid tyre size	18.00 R 25
Alternative size 1	505/95R25
LI / SI / PR	204 A2 / 185 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 741
TRA Code	E4
Star Rating	**
Carcass properties	H.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	462,90
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	8,00
Section width (mm)	500
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	737
Rolling circumference [mm].	5052
Tread depth (mm)	54,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
204 A2	16000	10		8,00	
185 B	9250	50		8,00	