Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10485051	
Valid tyre size	20.5 R 25	
LI / SI / PR	193 A2	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 755	



Notes and features

- The Windpower W755 has a durable L-5 tread pattern for . demanding applications.
- The cut- and puncture-resistant tread compound ensures ٠ a long service life for the tyre.
- The robust sidewalls provide very good stability.
- The tyre is best suited for wheel loaders on construction • sites, in recycling operations as well as tunnelling and mining.
- Attention: only approved for mounting on multi-part rim. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	10485051
EAN	4040658056246
Valid tyre size	20.5 R 25
Alternative size 1	525/80R25
LI / SI / PR	193 A2
TL/TT	тι
Brand	Windpower
Tread pattern	W 755
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	406,10
Recommended rim size	17.00/2.0
Maximum air pressure [bar].	6,00
Section width (mm)	520
Outer diameter of tyre [mm].	1572
Tread depth (mm)	72,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 A2	11500	10		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.