

TYRES

Product group	Tyres	
Item number	10485065	
Valid tyre size	550 / 65 R 25	
LI / SI / PR	182 A2 / 170 B	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 737	





Notes and features

- High traction, directionally-optimised tread pattern with wide contact area and optimum self-cleaning properties.
- Optimised tread pattern compound.
- Reduction of vibrations for better operational comfort and increased stability.
- Suitable for wheel loaders, dumpers, graders & bulldozers.
- Attention: mounting on multi-piece rim only.
- High traction, directionally-optimised tread pattern with wide contact area and optimum self-cleaning properties.



Technical Informations

Item number	10485065
EAN	4040658057038
Valid tyre size	550 / 65 R 25
LI / SI / PR	182 A2 / 170 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 737
TRA Code	E3
Star Rating	**
Carcass properties	H.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	304,80
Recommended rim size	17.00/2.0
Maximum air pressure [bar].	4,75
Section width (mm)	546
Outer diameter of tyre [mm].	1420
Stat. radius (SLR) [mm]	625
Rolling circumference [mm].	4283
Tread depth (mm)	44,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10	Loader dozer	4,75	
170 B	6000	50	Transport	4,25	