

TYRES

Product group	Tyres
Item number	10485100
Valid tyre size	650 / 65 R 25
LI / SI / PR	193 A2 / 180 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 733



WINDPOWER
Get Your Job Done

Notes and features

- High traction tread pattern with extra wide contact area.
- The combination of transversal and longitudinal grooves offers excellent grip, high ride comfort and self-cleaning.
- Optimised tread pattern compound.
- Extra-sturdy and durable rubber compound.
- Suitable for wheel loaders, dumpers & graders.
- Only approved for mounting on multi-part rim.

Technical Informations

Item number	10485100
EAN	4040658057045
Valid tyre size	650 / 65 R 25
LI / SI / PR	193 A2 / 180 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 733
TRA Code	E3
Star Rating	**
Carcass properties	H.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	320,70
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	4,75
Section width (mm)	650
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	658
Tread depth (mm)	38,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 A2	11500	10	Loader dozer	4,75	
180 B	8000	50	Transport	4,25	