

TYRES

Product group	Tyres
Item number	10485108
Valid tyre size	23.5 R 25
LI / SI / PR	185 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 745



WINDPOWER
Get Your Job Done

Notes and features

- High traction E-4 tread pattern with 150% tread pattern depth for a long tyre life.
- Rugged sidewall for increased stability.
- Low-cut and low-wear rubber compound with optimal self-cleaning properties.
- Heat-resistant rubber compound, specially designed for transport applications on articulated dumpers & graders such as levellers.
- Attention: mounting on multi-piece rim only.

Technical Informations

Item number	10485108
EAN	4040658056260
Valid tyre size	23.5 R 25
Alternative size 1	605/80R25
LI / SI / PR	185 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 745
TRA Code	E4
Star Rating	**
Carcass properties	H.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	398,00
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	4,75
Section width (mm)	600
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	726
Rolling circumference [mm].	4976
Tread depth (mm)	47,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 B	9250	50		4,75	