

TYRES

Product group	Tyres
Item number	10485115
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 753



WINDPOWER
Get Your Job Done

Notes and features

- Extra deep L-5 tyre with an aggressive tread design for outstanding traction on challenging surfaces.
- Robust sidewall for increased stability.
- Cut- and puncture-resistant tread compound.
- Good self-cleaning properties.
- Most suitable for use on wheel loaders, graders and levellers.
- Attention: mounting on multi-piece rim only.

Technical Informations

Item number	10485115
EAN	4040658057069
Valid tyre size	23.5 R 25
Alternative size 1	605/80R25
LI / SI / PR	201 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 753
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	486,50
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	6,00
Section width (mm)	600
Outer diameter of tyre [mm].	1704
Stat. radius (SLR) [mm]	750
Tread depth (mm)	78,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
201 A2	14500	10		6,00	