

TYRES

Product group	Tyres
Item number	10485119
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2 / 185 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 732





Notes and features

- The Windpower W 732 in the E3**/L3** version is a tyre for wheel loaders and dumpers.
- The tyre provides first-class traction on difficult surfaces and high stability.
- Thanks to its cut-resistant rubber compound, the tyre is perfectly protected against cuts.
- Attention: only approved for mounting on multi-part rim.



Technical Informations

Item number	10485119
EAN	4040658091001
Valid tyre size	23.5 R 25
Alternative size 1	605/80R25
LI / SI / PR	201 A2 / 185 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 732
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	329,00
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	6,00
Section width (mm)	600
Outer diameter of tyre [mm].	1620
Tread depth (mm)	35,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
201 A2	14500	10		6,00	
185 B	9250	50		4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.