

TYRES

Product group	Tyres
Item number	10485122
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 753



WINDPOWER
Get Your Job Done

Notes and features

- Extra deep L-5 tyre with an aggressive tread design for outstanding traction on challenging surfaces.
- Robust sidewall for increased stability.
- Cut- and puncture-resistant tread compound.
- Good self-cleaning properties.
- Most suitable for use on wheel loaders, graders and levellers.
- Attention: mounting on multi-piece rim only.

Technical Informations

Item number	10485122
EAN	4040658055836
Valid tyre size	26.5 R 25
Alternative size 1	685/80R25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 753
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	606,40
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,00
Section width (mm)	676
Outer diameter of tyre [mm].	1805
Stat. radius (SLR) [mm]	794
Rolling circumference [mm].	5230
Tread depth (mm)	95,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,00	