

TYRES

Product group	Tyres
Item number	10485126
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 755



WINDPOWER
Get Your Job Done

Notes and features

- The Windpower W755 has a durable L-5 tread pattern for demanding applications.
- The cut- and puncture-resistant tread compound ensures a long service life for the tyre.
- The robust sidewalls provide very good stability.
- The tyre is best suited for wheel loaders on construction sites, in recycling operations as well as tunnelling and mining.
- Attention: only approved for mounting on multi-part rim.

Technical Informations

Item number	10485126
EAN	4040658056352
Valid tyre size	26.5 R 25
Alternative size 1	685/80R25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Windpower
Tread pattern	W 755
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	684,60
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,00
Section width (mm)	676
Outer diameter of tyre [mm].	1805
Tread depth (mm)	95,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,00	