

TYRES

Product group	Tyres	
Item number	10485131	
Valid tyre size	26.5 R 25	
LI / SI / PR	209 A2 / 193 B	
TL/TT	TL	
Brand	Windpower	
Tread pattern	W 732	





Notes and features

- The Windpower W 732 in the E3**/L3** version is a tyre for wheel loaders and dumpers.
- The tyre provides first-class traction on difficult surfaces and high stability.
- Thanks to its cut-resistant rubber compound, the tyre is perfectly protected against cuts.
- Attention: only approved for mounting on multi-part rim.



Technical Informations

Item number	10485131
EAN	4040658091049
Valid tyre size	26.5 R 25
Alternative size 1	685/80R25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Windpower
Tread pattern	W 732
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	440,90
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,00
Section width (mm)	674
Outer diameter of tyre [mm].	1760
Tread depth (mm)	38,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,00	
193 B	11500	50		4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.