Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|----------------|--|
| Item number | 10485145 | |
| Valid tyre size | 750 / 65 R 25 | |
| LI / SI / PR | 202 A2 / 190 B | |
| TL/TT | TL | |
| Brand | Windpower | |
| Tread pattern | W 733 | |





Notes and features

- High traction tread pattern with extra wide contact area.
- The combination of transversal and longitudinal grooves offers excellent grip, high ride comfort and self-cleaning.
- Optimised tread pattern compound.

- Extra-sturdy and durable rubber compound.
- Suitable for wheel loaders, dumpers & graders.
- Only approved for mounting on multi-part rim.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| | 10105115 |
|------------------------------|----------------|
| Item number | 10485145 |
| EAN | 4040658057076 |
| Valid tyre size | 750 / 65 R 25 |
| LI / SI / PR | 202 A2 / 190 B |
| TL/TT | ТL |
| Brand | Windpower |
| Tread pattern | W 733 |
| TRA Code | E3 |
| Star Rating | ** |
| Carcass properties | H.R. |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 456,10 |
| Recommended rim size | 24.00/3.0 |
| Maximum air pressure [bar]. | 4,75 |
| Section width (mm) | 750 |
| Outer diameter of tyre [mm]. | 1610 |
| Stat. radius (SLR) [mm] | 708 |
| Tread depth (mm) | 44,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 202 A2 | 15000 | 10 | Loader dozer | 4,75 | |
| 190 B | 10600 | 50 | Transport | 4,25 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.