Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	10485156	
Valid tyre size	29.5 R 25	
LI / SI / PR	216 A2	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WL 37	





Notes and features

- Aggressive tread pattern for excellent traction on demanding surfaces with very good self-cleaning properties.
- L-3D identifier: deeper tread pattern than a classic EM tyre with L3 identifier.
- Improved tread compound protects the tyre from wear and damages.
- Strong sidewall for increased stability.
- Especially suitable for wheel loaders.
- Attention: mounting on multi-piece rim only.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10485156
EAN	4040658076817
Valid tyre size	29.5 R 25
Alternative size 1	765/80R25
LI / SI / PR	216 A2
TL/TT	Т
Brand	Windpower
Tread pattern	WL 37
TRA Code	L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	569,09
Recommended rim size	25.00/3.5
Maximum air pressure [bar].	6,00
Section width (mm)	748
Outer diameter of tyre [mm].	1872
Stat. radius (SLR) [mm]	824
Rolling circumference [mm].	5646
Tread depth (mm)	48,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
216 A2	22400	10		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.