

## **TYRES**

Product group	Tyres
Item number	10626085
Valid tyre size	280 / 85 R 20
LI / SI / PR	112 D / 109 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



## Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



## **Technical Informations**

Item number	10626085
EAN	3286340562010
Valid tyre size	280 / 85 R 20
LI / SI / PR	112 D / 109 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	37,05
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	297
Outer diameter of tyre [mm].	978
Stat. radius (SLR) [mm]	442
Rolling circumference [mm].	2934
Tread depth (mm)	28,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	76.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 D	1120	65		1,60	
109 E	1030	70		1,60	