

## TYRES

Product group	Tyres
Item number	10626116
Valid tyre size	280 / 85 R 24
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL



## Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.

## Technical Informations

Item number	10626116
EAN	3286340412315
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	49,62
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	4,00
Section width (mm)	292
Outer diameter of tyre [mm].	1082
Stat. radius (SLR) [mm]	488
Rolling circumference [mm].	3328
Tread depth (mm)	33,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	87
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A8	1900	40		4,00	
130 B	1900	50		4,00	