

TYRES

Product group	Tyres
Item number	10626136
Valid tyre size	340 / 85 R 24
LI / SI / PR	136 A8 / 136 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.

Technical Informations

Item number	10626136
EAN	3286340412414
Valid tyre size	340 / 85 R 24
Alternative size 1	13.6R24
LI / SI / PR	136 A8 / 136 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,51
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	3,20
Section width (mm)	355
Outer diameter of tyre [mm].	1192
Stat. radius (SLR) [mm]	537
Rolling circumference [mm].	3600
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	141
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40		3,20	
136 B	2240	50		3,20	