

TYRES

Product group	Tyres	
Item number	10626154	
Valid tyre size	420 / 85 R 24	
LI / SI / PR	137 D / 134 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 85	



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10626154
EAN	3286340560313
Valid tyre size	420 / 85 R 24
Alternative size 1	16.9R24
LI / SI / PR	137 D / 134 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	87,80
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	446
Outer diameter of tyre [mm].	1323
Stat. radius (SLR) [mm]	595
Rolling circumference [mm].	3969
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	236.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 D	2300	65		1,60	
134 E	2120	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.