

## TYRES

Product group	Tyres
Item number	10626156
Valid tyre size	420 / 85 R 24
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.

## Technical Informations

Item number	10626156
EAN	3286340412513
Valid tyre size	420 / 85 R 24
Alternative size 1	16.9R24
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	96,68
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	2,40
Section width (mm)	446
Outer diameter of tyre [mm].	1323
Stat. radius (SLR) [mm]	596
Rolling circumference [mm].	3996
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	238.5
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		2,40	
142 B	2650	50		2,40	