

TYRES

Product group	Tyres
Item number	10626246
Valid tyre size	320 / 85 R 28
LI / SI / PR	124 D / 121 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10626246
EAN	3286340562911
Valid tyre size	320 / 85 R 28
Alternative size 1	12.4R28
LI / SI / PR	124 D / 121 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	54,70
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	330
Outer diameter of tyre [mm].	1257
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3771
Tread depth (mm)	38,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	127.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 D	1600	65		1,60	
121 E	1450	70		1,60	