

TYRES

Product group	Tyres
Item number	10626256
Valid tyre size	340 / 85 R 28
LI / SI / PR	127 D / 124 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10626256
EAN	3286340563017
Valid tyre size	340 / 85 R 28
Alternative size 1	13.6R28
LI / SI / PR	127 D / 124 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,50
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	354
Outer diameter of tyre [mm].	1302
Stat. radius (SLR) [mm]	585
Rolling circumference [mm].	3906
Tread depth (mm)	41,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	157.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 D	1750	65		1,60	
124 E	1600	70		1,60	