

TYRES

Product group	Tyres
Item number	10626376
Valid tyre size	460 / 85 R 34
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10626376
EAN	3286340563611
Valid tyre size	460 / 85 R 34
Alternative size 1	18.4R34
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	130,60
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	1,60
Section width (mm)	487
Outer diameter of tyre [mm].	1652
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	4956
Tread depth (mm)	50,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	382.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 D	3075	65		1,60	
144 E	2800	70		1,60	